

Self-Test Series Self-Testing Addressable Detectors

The breakthrough NOTIFIER[®] Self-Test Series intelligent plug-in smoke detectors are designed for performance, ease of use and aesthetics. When used with NOTIFIER INSPIRE™ Series N16 panel, the Self-Test Series detectors automatically perform maintenance tests of smoke and heat detection without using canned smoke or heat guns. The Self-Test process meets the three core NFPA requirements for detector maintenance: functional test, smoke entry test, and ability to verify a visual inspection has taken place. It is the first detector of its type to be approved by UL. It also retains the great features of the standard 951 series including the enhanced optical sensing chamber which is engineered to sense smoke produced by a wide range of combustion sources in accordance with more stringent code standards. For ease, its sensitivity can also be programmed in the control panel software. Sensitivity is continuously monitored and reported to the panel. Point ID capability allows each detector's address to be set with rotary, decimal address switches, providing exact detector location for selective maintenance when chamber contamination reaches an unacceptable level. Dual electronic thermistors add 135°F (57°C) fixed temperature thermal sensing on the FSP-951T-SELFT. The NOTIFIER Self-Test series detectors are available for our FlashScan[®] applications.

Features

SELF-TEST

- Introduces small amounts of smoke and heat into the chamber to test both sensors
- Automatically tests if the photo sensor smoke entry points are blocked by the dust cover
- Verifies that the technician has completed the visual inspection through its built-in beacon and the self test app
- Tests detectors across multiple loops and panels concurrently
- Listed to UL 268 7th edition and/or UL 521

SLC LOOP

- Two-wire SLC loop connection
- Unit uses base for wiring
- Compatible with FlashScan[®] protocol systems
- Stable communication technique with noise immunity

ADDRESSING

- Addressable by device
- Rotary, decimal addressing
(Refer to the NOTIFIER panel manuals for device capacity.)

ARCHITECTURE

- Sleek, low-profile, stylish design
- Unique single-source design to respond quickly and dependably to a broad range of fires
- Integral communications and built-in device-type identification
- Tamper resistance option provided by bases
- Remote test feature from the panel
- Built-in functional test switch activated by external magnet
- Removable cover and insect-resistant screen for simple field cleaning

OPERATION

- LED "blinks" when the unit is polled (communicating with the fire panel) and latches in alarm.
- Low standby current



MECHANICALS

- Sealed against back pressure
- SEMS screws for wiring of the separate base
- Designed for direct-surface or electrical-box mounting
- Plugs into separate base for ease of installation and maintenance

OPTIONS

- Optional relay, isolator, and sounder bases

Installation

NOTIFIER Self-Test Series plug-in intelligent smoke detectors use a detachable base to simplify installation, service and maintenance. Installation instructions are shipped with each detector.

Mount detector base (all base types) on an electrical backbox which is at least 1.5" (3.81 cm) deep. For a chart of compatible junction boxes, see *DN-60054*.

NOTE: Because of the inherent supervision provided by the SLC loop, end-of-line resistors are not required. Wiring "T-taps" or branches are permitted for Class "B" wiring only.

When using relay or sounder bases, consult the ISO-X/ISO-XA manuals for device limitations between isolator modules and isolator bases.

Construction

These detectors are constructed of fire-resistant plastic. NOTIFIER[®] Self-Test Series plug-in intelligent smoke detectors are designed to commercial standards and offer an attractive appearance.

Operation

Each NOTIFIER Self-Test Series detector uses one of the panel's addresses on the NOTIFIER Signaling Line Circuit (SLC). The detector responds to regular polls from the control panel and reports its type and the status. If it receives a test command from the panel (or a local magnet test), it stimulates its electronics and reports an alarm. It blinks its LEDs when polled and turns the LEDs on when commanded by the panel. The NOTIFIER Self-Test Series offers an industry breakthrough with its UL approved Self-Test feature as well as great fire detection performance that represent the latest in smoke detector technology.

Product Line Information

FSP-951-SELFT: White, low-profile intelligent self-testing photo-electric sensor, FlashScan only

FSP-951T-SELFT: White, same as FSP-951 but includes a built-in 135°F (57°C) fixed-temperature thermal device, FlashScan only

FST-951-SELFT: White, low-profile intelligent self-testing 135°F fixed thermal sensor, FlashScan only

INTELLIGENT BASES

NOTE: For details on intelligent bases, see DN-60054.

B300-6: White, 6" base, standard flanged low-profile mounting base (CSFM: 7300-1653:0109)

B300-6-IV: Ivory, 6" base, standard flanged low-profile mounting base (CSFM: 7300-1653:0109)

B300-6-BP: Bulk pack of B300-6, package contains 10

B501-WHITE: White, 4" standard European flangeless mounting base. UL listed (CSFM: 7300-1653:0109)

B501-BL: Black, 4" standard European flangeless mounting base. UL listed (CSFM: 7300-1653:0109)

B501-IV: Ivory, 4" standard European flangeless mounting base. UL listed (CSFM: 7300-1653:0109)

B501-WHITE-BP: Bulk pack of B501-WHITE contains 10

B224RB-WH: White, relay base (CSFM: 7300-1653:0216)

B224RB-IV: Ivory, relay base (CSFM: 7300-1653:0216)

B224BI-WH: White, isolator detector base (CSFM: 7300-1653:0216)

B224BI-IV: Ivory isolator detector base (CSFM: 7300-1653:0216)

B200S-WH: White, Intelligent addressable sounder base capable of producing sound output in high or low volume with ANSI Temporal 3, ANSI Temporal 4, continuous tone, marching tone, and custom tone. Uses FlashScan protocol. (CSFM: 7300-1653:0213)

B200S-IV: Ivory, Intelligent addressable sounder base capable of producing sound output in high or low volume with ANSI Temporal 3, ANSI Temporal 4, continuous tone, marching tone, and custom tone. Uses FlashScan protocol. (CSFM: 7300-1653:0213)

B200S-LF-WH: White, Low Frequency Intelligent, programmable sounder base. Produces a fundamental frequency of 520 Hz +/-10% with a square wave or its equivalent; designed to meet the NFPA 72 sleeping space requirement. (CSFM: 7300-1653:0238)

B200S-LF-IV: Ivory, Low Frequency Intelligent, programmable sounder base. Produces a fundamental frequency of 520 Hz +/-10% with a square wave or its equivalent; designed to meet the NFPA 72 sleeping space requirement. (CSFM: 7300-1653:0238)

B200SR-WH: White, Intelligent sounder base capable of producing sound output with ANSI Temporal 3 or continuous tone. Intended for retrofit applications. (CSFM: 7300-1653:0213)

B200SR-IV: Ivory, Intelligent sounder base capable of producing sound output with ANSI Temporal 3 or continuous tone. Intended for retrofit applications. (CSFM: 7300-1653:0213)

B200SR-LF-WH: White, Low Frequency Intelligent, programmable sounder base. Produces a fundamental frequency of 520 Hz +/-10% with a square wave or its equivalent; designed to meet the NFPA 72 sleeping space requirement. Intended for retrofit applications. (CSFM: 7300-1653:0238)

B200SR-LF-IV: Ivory, Low Frequency Intelligent, programmable sounder base. Produces a fundamental frequency of 520 Hz +/-10% with a square wave or its equivalent; designed to meet the NFPA 72 sleeping space requirement. Intended for retrofit applications. (CSFM: 7300-1653:0238)

MOUNTING KITS AND ACCESSORIES

TR300: White, replacement flange for B300-6 series bases

TR300-IV: Ivory, replacement flange for B300-6 series bases

RA100Z: Remote LED annunciator. 3-32 VDC. Mounts to a U.S. single-gang electrical box. For use with B501 and B300-6 series bases.

M02-04-00: Test magnet

M02-09-00: Test magnet with telescoping handle

CK300: Color Kit (includes cover and trim ring), white, 10-pack, for use with FST-951-SELFT only

CK300-IV: Color Kit (includes cover and trim ring), ivory, 10-pack, for use with FST-951-SELFT only

CK300-BL: Color Kit (includes cover and trim ring), black, 10-pack, for use with FST-951-SELFT only

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

Voltage range: 15 - 32 volts DC peak

Standby current (max. avg.): 200 μ A @ 24 VDC (one communication every 5 seconds with LED enabled)

Max current: 4.5 mA @ 24 VDC ("ON")

PHYSICAL SPECIFICATIONS

Sensitivity:

- UL Applications:
 - Open Area: 2.86 - 5.0 %/FT obscuration
 - Special Application: 0.5 - 2.86 %/FT obscuration

Size: 2.0" (51mm) high; base determines diameter

- **B300-6 series:** 6.1" (15.6 cm) diameter
- **B501 series:** 4" (10.2 cm) diameter

For a complete list of detector bases see DN-60054

Shipping weight: 3.4 oz. (95 g)

Operating temperature range:

- FSP-951-SELFT: 32°F to 122°F (0°C to 50°C)
- FSP-951T-SELFT: 32°F to 115°F (0°C to 47°C)
- FST-951-SELFT:
 - Set for fixed-temperature or rate-of-rise (ROR): -4°F to 100°F (-20°C to 38°C)
 - Set for high-heat: -4°F to 150°F (-20°C to 66°C)

UL Listed Velocity Range: 0-4000 ft/min. (1219.2 m/min.). Velocity range with Self-Test process in operation: 0-300 ft/min (91.4 m/min).

Relative humidity: 10% – 93% non-condensing

Thermal ratings: fixed-temperature set point 135°F (57°C), rate-of-rise detection 15°F (8.3°C) per minute, high temperature heat 190°F (88°C)

Self-Test Operation: The Self-Test feature offers up to 150 tests before reaching an end of life.

Mounting: To ensure the operation of the Self-Test feature, a detector installed on the ceiling must remain in a ceiling-oriented position; those installed on the wall must remain in a wall-oriented position.

Detector Spacing and Applications: NOTIFIER recommends spacing detectors in compliance with NFPA 72. For specific information regarding detector spacing, placement, and special applications refer to NFPA 72. A *System Smoke Detector Application Guide*, document SPAG91, is available at www.systemsensor.com.

STANDARDS

- **UL268 7th edition** (FSP-951-SELFT, FSP-951T-SELFT)
- **UL521** (FSP-951T-SELFT, FST-951-SELFT)

Listings and Approvals

Listings and approvals below apply to the Self-Test Series detectors. In some cases, certain modules may not be listed by certain approval agencies, or listing may be in process. Consult factory for latest listing status.

- **UL Listed:** S1115
- **CSFM:** 7270-0028:0502 (FST-951-SELFT), 7272-0028:0503 (FSP-951-SELFT, FSP-951T-SELFT)



This document is not intended to be used for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

NOTIFIER INSPIRE™ is a trademark of and FlashScan®, NOTIFIER®, and System Sensor® are registered trademarks of Honeywell International, Inc.

©2021 by Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited.

Country of Origin: Mexico

NOTIFIER

12 Clintonville Road
Northford, CT 06472
203.484.7161
www.notifier.com

